

Headquarters

**SPEKTRA Schwingungstechnik und
 Akustik GmbH Dresden**

Heidelberger Str. 12
 01189 Dresden
 Germany



Telephone: +49 351 400 24 0
Fax: +49 351 400 24 99
Email: sales@spektra-dresden.com
Web: www.spektra-dresden.com

US Office

SPEKTRA USA

32124 Paseo Adelanto, Suite 3
 San Juan Capistrano, CA 92675



Telephone: +1-949-234-9791
Fax: +1-760-683-3184
Email: sales@spektra-usa.com
Web: www.spektra-usa.com



**Rugged & mobile
 vibration calibrator**



CV=10

USER FRIENDLY

LOW INVESTMENT COSTS

FUTURE PROOF



Extensive, portable and lightweight. Traceable to NIST and PTB.

Flexible signal conditioners

- ✓ PE, IEPE, 20 mA current
- ✓ amplifier for PR transducers*
- ✓ extension port for future options

Powerful vibration exciter

- ✓ 5 Hz ... 10 kHz
- ✓ up to 200 m/s²
- ✓ up to 900 g (1.98 lb) payload

Reliable reference transducer

- ✓ reference transducer inside vibration exciter
- ✓ external back-to-back transducer*

Enhanced connectivity

- ✓ USB data exchange
- ✓ ethernet connection for PC software
- ✓ Wi-Fi (option)

High-performance operation

- ✓ manual mode with presets
- ✓ automatic stepped sine
- ✓ automatic sweep*
- ✓ high-resolution color display

Variable power supply

- ✓ 100 V ... 240 V
- ✓ battery operation up to 10 h

(* = option)

